

Scheda tecnica: HPC235CPR

Datasheet:



Categoria: Cavo microfonico bilanciato a bassa capacità – CPR in classe Cca
Category: Low capacity balanced microphone cable – CPR Cca Class

Applicazioni: Collegamenti microfonici ed Audio per installazioni fisse – Interno edificio
Applications: Microphone and Audio connections for fixed installations - Indoor



Marcatura / Printing on the cable:

>>> PROEL (logo) HPC235CPR 2x0,35 mm² - Audio cable for fixed Installation - 51/24 nr. 4400023148 - CE / UKCA - LSZH Cca s1a,d1,a1 — Made in Italy >>>

Guaina: LSZH di colore NERO – Ø esterno 6,2 mm ± 0,2

Jacket: Black L.S.Z.H. – – Ø 6,2 mm ± 0,2 outer

Schermo: Nastro in PET/alluminio con copertura 100% + drain wire 7*0,25 rame stagnato

*Shield: PET/aluminium tape with 100% coverage + 7*0.25 tinned copper drain wire*

Isolamento: Isolamento dei conduttori L.S.Z.H. bianco e rosso - Ø 1,8 mm ± 0,15

Insulation: L.S.Z.H. Cores insulation, colored one red and one white - Ø 1,8 mm ± 0,15

Conduttori: 7 * 0,25 mm in Rame Stagnato – Sezione nominale 2 * 0,35 mm²

*Cores: 7 * 0,25 mm Tinned Copper – Nominal Cross section 2 * 0,35 mm²*

Tensione nominale di funzionamento (V): 100

Nominal working tension (V): 100

Tensione di prova (V): 2000

Testing tension (V): 2000

Temperatura massima di esercizio (°C): +70

Maximum operating temperature (°C): +70

Temperatura minima di posa (°C): +5

Minimum installation temperature (°C): +5

Temperatura minima di esercizio/posa fissa (°C): -20

Fixed minimum operating/installation temperature (°C): -20

Resistenza a 20 °C (Ohm/Km): in accordo alla norma IEC 225/HD383 S2 (CEI 20-29)

Resistance at 20 °C (Ohm/Km): in accordance with IEC 225/HD383 S2 (CEI 20-29) standard

Resistenza alla fiamma: in accordo alla norma IEC 60332-1-2 (CEI 20-35)

Flame resistance: in accordance with IEC 60332-1-2 (CEI 20-35) standard

Norme Generali: BT 93/68 CEE – 2014/35/EU – 2011/65/CE (RoHS II) – 2015/863/EU (RoHS 3)

General rules: 2006/1907/ce (Reach) – Reg. 2016/217

CPR 305/2011 EN 50575

Reazione al fuoco: Cca; S1a, d1, a1 - Dangerous sub.s: none

Reaction to fire: